

H503 GLOW

GLOWING SMOKE GENERATOR



The **H503 GLOW** for natural wood chips is suitable for Hot-Smoking Installations with a capacity of up to 12 trolleys as well as Climatic Maturing Installations with up to 80 trolleys.



TECHNICAL DETAILS

- 1. MAXIMUM USER FRIENDLINESS & SIMPLE OPERATION**
 - Individual adjustment via a user-friendly compact control unit.
- 2. TOP ENERGY EFFICIENCY**
 - Shorter heat-up and faster smoking times due to high smoke concentration - 30% energy savings.
- 3. CAPTIVATING QUALITY**
 - Temperature monitoring with an integrated extinguishing device and water pressure check ensure a smooth production process.
- 4. OUTSTANDING HYGIENE**
 - No smoke nuisance during the production process due to a closed system providing highest safety.



DIMENSIONS

DEPTH	WIDTH	HEIGHT	HOPPER
1090 mm	645 mm	1900 mm	640 x 450 mm

ENERGY VALUES

ELECTRICAL RATING	WATER RATING	WASTE WATER CONNECTION	SMOKE TUBE CONNECTION
2 kW 400, 230, 440, 575 V 50/60 Hz 3Ph	3-4 bar	DN32	DN125

MISC.

QUANTITY OF SMOKE	REQUIREMENT OF FRESH AIR	HOPPER VOLUME	WEIGHT
120 m ³ /h	250 m ³ /h	180 l	550 kg